

THICK FILM CHIP RESISTOR ARRAYS

- CN SERIES -


FEATURES

- Small size and light weight, high density
- Reduction of assembly costs and matching with placement machines (automatic lacement)
- Reliability, high quality
- Suitable for IR reflow soldering
- Convex

APPLICATIONS

- Entertainment
- Computer & Related Products
- Communication Equipment
- Power Equipment
- Measuring Equipment



DIMENSIONS



UNIT=mm

TYPE	L	W	t	P	a	b	c
CN22	1.0±0.1	1.0±0.1	0.35±0.1	0.65±0.05	0.3±0.1	0.15±0.1	0.25±0.2
CN24	2.0±0.1	1.0±0.1	0.4±0.2	0.5±0.05	0.3±0.1	0.15±0.1	0.25±0.2
CN34	3.2±0.1	1.6±0.15	0.55±0.1	0.8±0.5	0.45±0.1	0.3±0.2	0.3±0.2

CONSTRUCTION



PART NUMBER GUIDE

CN	34	F	1001	CT
PRODUCT TYPE	SERIES	RESISTANCE TOLERANCE	RESISTANCE	PACKAGING
	22 - 0402X2 4P2R 24 - 0402X4 8P4R 34 - 0603X4 8P4R	F: ±1% J: ±5%	5% = 3 Digit 1st 2 significant, 3rd is multiplier by (10x) 1% = 4 Digit 1st 3 significant 4th is multiplier by (10x)	CT: Tape and Reel

RATED VOLTAGE


The value of rated voltage shall be determined from formula (1).

$$E = \sqrt{P \times R} \dots\dots(1)$$


E = Rated Voltage (V) P - Power Rating (W)

R = Nominal Resistance (Ω)

DERIVATIVE CURVE



The resistors operated in ambient temperatures above 70°C, power rating must be derated in accordance with curve above.





FEATURES

ITEM	SPECIFICATIONS	TEST METHODS
Temperature Coefficient	TCR: ± 200 ppm	Inspection Temp. Cold: $+25^{\circ}\text{C} \sim -55^{\circ}\text{C}$ Hot: $+25^{\circ}\text{C} \sim +125^{\circ}\text{C}$
Short Time Overload	$\pm(2\%+0.05\Omega)$	1. Apply 2.5 x rated voltage for 5 sec. 2. Wait 30 minutes 3. Measure resistance value
Load Life	$\pm(3\%+0.05\Omega)$	1. Dwell in chamber at $70\pm 2^{\circ}\text{C}$ for ON:90 min. at rated voltage; then off: 30 min. 2. Perform 1,000 hours cyclically
Load Life in Humidity	$\pm(3\%+0.05\Omega)$	1. Dwell in humidity chamber at $40\pm 2^{\circ}\text{C}$ and 95% RH for ON:90 min. at rated voltage; then off: 30 min. 2. Perform 1,000 hours cyclically
Temperature Cycling	$\pm(1\%+0.05\Omega)$	1. $-55\pm 3^{\circ}\text{C}$, make 5 cycles 2. Released 1 hour in room temp., then measure value.
Effect of Soldering	$\pm(2.5\%+0.05\Omega)$ - Non-damage by machinery	1. Immersed in molten solder at $270\pm 5^{\circ}\text{C}$ for 10 ± 0.1 sec. 2. Released 1 hour in room temp., then measure value.
Solderability	95% coverage min.	1. Immersed in rosin solution for 5-10 seconds. 2. Re-immersed in solder pot at $230\pm 5^{\circ}\text{C}$ for 3 ± 0.5 sec
Intermittent Overload	$\pm(5\%+0.1\Omega)$	1. perform 10,000 voltage cycles as follows: ON (2.5 x rated voltage or current) 1 sec. and OFF 25 sec. 2. Released 30 min without loading 3. Measure resistance
Dielectric Withstanding Voltage	No evidence of mechanical damage	Apply 300VAC for 1 second
Insulation Resistance	$10^8 \Omega$ min	Apply 100VDC

PACKAGING

REEL SPECIFICATIONS & PACKAGING QUANTITY





TYPE	A	B	C	D	E	W1	W2
CN22	$\varnothing 178\pm 2.0$	$\varnothing 80\pm 2.0$	$\varnothing 13\pm 0.5$	$\varnothing 21.0$	2.0 ± 0.5	9.0 ± 1.0	11.4 ± 2.0
CN24	$\varnothing 178\pm 2.0$	$\varnothing 80\pm 2.0$	$\varnothing 13\pm 0.5$	$\varnothing 21.0$	2.0 ± 0.5	10.0 ± 1.0	12.5 ± 1.0
CN34	$\varnothing 178\pm 2.0$	$\varnothing 80\pm 2.0$	$\varnothing 13\pm 0.5$	$\varnothing 21.0$	2.0 ± 0.5	10.0 ± 1.0	12.5 ± 1.0

UNIT=mm

The top fixed tape for each carrier shall have an adhesion peel strength of 10 to 50G, measure method is shown above to peel away.

TAPING SPECIFICATION



TYPE		A	B	C	D	E	F	G	H	J	t
CN22	10000	2.0 ± 0.15	2.4 ± 0.2	8.0 ± 0.2	3.5 ± 0.05	1.75 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	4.0 ± 0.1	$.5\pm 0.1/-0$	$.84\pm 0.01$
CN24	10000	2.0 ± 0.15	2.4 ± 0.2	8.0 ± 0.2	3.5 ± 0.05	1.75 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	4.0 ± 0.1	$.5\pm 0.1/-0$	$.84\pm 0.01$
CN34	5000	2.0 ± 0.2	3.6 ± 0.2	8.0 ± 0.1	3.5 ± 0.05	1.75 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	4.0 ± 0.1	1.5 ± 0.1	1.0

UNIT=mm

