

SMD ALUMINUM ELECTROLYTIC

- CV SELECTOR GUIDE -

SERIES	FEATURES	TEMP & LOAD LIFE TIME	RATED VOLTAGE RANGE	CAPACITANCE RANGE
CV2	Miniaturized, Big Capacitance	85°, 2,000 hrs	6.3~100	0.1 ~ 1,500
CV3*	High Capacitance & High Voltage	85°, 2,000 hrs	6.3~450	0.1 ~ 6,800
CVC	Low Leakage Current	85°, 2,000 hrs	6.3~50	0.1 ~ 100
CVB	Bi-polarized	85°, 2,000 hrs	6.3~50	0.1 ~ 47
CVS	Miniaturized, 105°	105°, 1,000 Hrs	6.3~50	0.1 ~ 100
CVL	Long Life, 105°, 5.7mmL	105°, 3,000 Hrs	6.3~50	0.1 ~ 1,000
CVG	Higher Capacitance Range	105°, 2,000 Hrs	6.3~450	0.1 ~ 6,800
CVJ	Long Life, 105°	105°, 2,000 Hrs	6.3~100	10 ~ 470
CVY	Low Impedance & ESR	105°, 2,000 Hrs	6.3~35	4.7 ~ 1,000
CVZ	Low Impedance & ESR Smaller Size	105°, 1,000 Hrs	6.3~50	1 ~ 220
CVH	Low Impedance & ESR, Long Life	105°, 2,000~5,000 Hrs	6.3~100	1 ~ 4,700
CVK	Long Life, 105°	105°, 2,000~5,000 Hrs	6.3~50	0.1 ~ 470
CVU	High temp	125°, 1,000 Hrs	6.3~50	33 ~ 1,000

* Please note that the old CV5 series has been incorporated into the CV3's newer expanded range